

## **DMX512 Fountain Pumps**

## GROW YOUR BUSINESS WITH US



Fuyong town, Baoan District Shenzhen, 518000, China



CONTACT

Email: sales@bldcpump.com Phone: +86 755 8526 1096

Website: https://www.bldcpump.com/ https://dcwaterpump.com/

#### **ABOUT BLDC PUMP**

#### What We Do

BLDC PUMP focused on brushless DC water pump's R&D and production from 2009. Our high-quality brushless DC pumps are primarily used in various types of equipment as an essential component. It has high efficiency & high durability with a compact size and is very quiet. We are located in Shenzhen of China, and export our products all over the world.

#### **Our Values**

While most companies pursue low costs to win at a price, we insist on providing the best quality products and comprehensive solutions to help our clients push their business forward.

Our competitive benefit lies in our offer of growth insights for professional pump solutions to power revenues and profits your business. We will serve as a stepping stone, assist you to make a leap from "Zero to One" in your new business.

We face a variety of problems from our customers on a daily basis. We love these problems and love solving these problems more. Because we helped our customers, and the process also made us more and more professional.

We have 10 Years of expertise in DC Water Pump's R&D and production. Therefore, we can make flexible and cost-effective customized services according to your actual needs.



#### **DMX512 Fountain Pumps Overview**

DMX512 fountain pumps are designed for small or medium music fountains that could receive DMX512 signals directly to control the water column. No need additional DMX512 signal decoder.

Two other advantages of using our fountain pumps:


- 1. low voltage DC water pump is absolute safety
- 2. We provide accurate data of water column height according to different nozzles and pump models

Get more information: https://www.bldcpump.com/dmx512-small-water-fountain-pump/

#### **DMX512 Fountain Pumps Wiring Instructions**

Brown: Pump Power (+) Blue: Pump Power (-) Red: DMX DATA (+) Black: Ground

Yellow: DMX DATA (-)





#### **CONTENT**

DMX512 Fountain Pumps Overview ······	3
DMX512 Fountain Pumps Wiring Instructions	3
The Nozzles we use to test data	5
DMX512 Fountain Pump DC55E-24160S ······	6
DMX512 Fountain Pump DC60E-24120S ······	8
DMX512 Fountain Pump DC80E ······ 1	11
DMX512 Fountain Pump DC85E ····································	I 4

#### The Nozzles we use to test data

We have accurate data of water column height when using the following nozzles with our fountain pumps. But please note that you can use any nozzle you want.










### **DMX512 Fountain Pump DC55E-24160S**





#### **Pump Main Parameters**

Model:	DC55E-24160S
Rated Voltage:	DC24V
Power	80W
Max Static Head:	16 meters
Max Flow Rate:	2400 L/H
Input / Output:	1/2" thread

Please note that we need an additional connector for conversion when the nozzle inlet does not match the pump outlet.






Nozzle	Universal DN15 outlet 5.6mm	Universal DN20 outlet 6.8mm	
Spray Height	6 Meters	5 Meters	

## **DMX512 Fountain Pump DC60E-24120S**





#### **Pump Main Parameters**

Model:	DC60E-24120S
Rated Voltage:	DC24V
Power	120W
Max Static Head:	12 meters
Max Flow Rate:	3800 L/H
Input / Output:	1/2" thread
















Nozzle	Universal	Universal	Straight	Straight	Universal	Universal	Universal
	DN15	DN20	DN20	DN25	DN25	DN25	DN25
	outlet 5.6mm	outlet 6.8mm	outlet 19mm	outlet 20mm	outlet 8mm	outlet 10mm	outlet 12mm
Spray Height	6 Meters	5.5 Meters	3 Meters	1.5 Meters	5 Meters	3.5 Meters	2.5 Meters

### **DMX512 Fountain Pump DC80E**





#### **Pump Main Parameters**

Model:	DC80E-2480S / DC80E-24100S
Rated Voltage:	DC24V
Power	100W / 150W
Max Static Head:	8 meters / 10 meters
Max Flow Rate:	7000 L/H / 8000L/H
Input / Output:	1" thread


















Nozzle	Model	Straight DN20 outlet 19mm	Straight DN25 outlet 20mm	ICE Tower DN25 outlet 32mm	Universal DN25 outlet 8mm
Convey Height	DC80E-2480S	4 Meters	2.5 Meters	1 Meters	5 Meters
Spray Height	DC80E-24100S	4 Meters	3 Meters	1.5 Meters	6.5 Meters
Nozzle	Model	Universal DN25 outlet 10mm	Universal DN25 outlet 12mm	Universal DN40 outlet 13mm	Universal DN40 outlet 16mm
Spray Height	DC80E-2480S	4.5 Meters	4 Meters	3.5 Meters	2.5 Meters
	DC80E-24100S	5.5 Meters	5 Meters	4.5 Meters	3.5 Meters

### **DMX512 Fountain Pump DC85E**



#### **Pump Main Parameters**

Model:	DC85E-2480S / DC85E-24100S
Rated Voltage:	DC24V
Power	150W / 200W
Max Static Head:	8 meters / 10 meters
Max Flow Rate:	12000 L/H / 13000L/H
Input / Output:	1- <sup>1</sup> / <sub>4</sub> " thread















Nozzle	Model	Straight DN25 outlet 20mm	ICE Tower DN25 outlet 32mm	Universal DN40 outlet 13mm	Universal DN40 outlet 16mm
Convey Heimba	DC85E-2480S	3 Meters	1.3 Meters	3.5 Meters	2.5 Meters
Spray Height	DC85E-24100S	4 Meters	1.8 Meters	5 Meters	4 Meters
Nozzle	Nozzle Model		Universal DN25 outlet 10mm	Universal DN25 outlet 12mm	
Spray Height	DC85E-2480S	4.5 Meters	4 Meters	3.5 Meters	
	DC85E-24100S	6 Meters	5.5 Meters	5 Meters	



# PRODUCT CATALOG 2021



Email: sales@bldcpump.com Phone: +86 755 8526 1096 Add: Baoan, Shenzhen, China



Scan for download the Latest DMX512 Fountain Pumps Catalog

Direct Link:

https://www.bldcpump.com/downloads/dmx512-fountain-pumps.pdf